

MATERIAL SAFETY DATA SHEET

P.V. SPECIAL - Page 1 of 2

Conforms to OSHA Hazard Communication Standard 29CFR 1910.1200

June 1998

PRODUCT IDENTIFICATION

Trade name: P.V. Special

Standard Ceramic Supply Co.
P.O. Box 4435
Pittsburgh, PA 15205-0435

Telephone: 412-276-6333
Fax: 412-276-7124
e-mail: standardceramic@msn.com

HAZARDOUS INGREDIENTS

Free Silica (Crystalline Quartz) Formula: SiO₂ CAS: 14808-60-7

PHYSICAL DATA

Boiling Point:	Vapor Pressure:	Specific Gravity:
Not Applicable	Not Applicable	2.40-2.65
Melting Point:	Solubility in Water:	Percent Volatile:
1100-1450C	Insoluble	Not Applicable
Odor and Appearance:		

HEALTH HAZARD INFORMATION

OSHA PEL: CRYSTALLINE QUARTZ (Respirable) 0.1 mg/m³ (TWA-TLV)

ACGIH TLV: CRYSTALLINE QUARTZ (Respirable) 0.1 mg/m³ (TWA-TLV)

NIOSH TWA: CRYSTALLINE QUARTZ (Respirable) 0.05 mg/m³

HAZARD BY ROUTES OF EXPOSURE:

INHALATION: **WARNING:** These products contain crystalline silica. Repeated, prolonged inhalation of dust may cause delayed lung injury which may result in silicosis or pneumoconiosis. The International Agency For Research On Cancer in its publication, "IARC Monographs On The Evaluation Of The Carcinogenic Risk To Humans - Silica, Some Silicates, Coal Dust and Para-aramid Fibrils" - Volume 68, 1997, has concluded that there is sufficient evidence for the carcinogenicity of crystalline silica in humans, and has, therefore, classified crystalline silica in Group 1, carcinogenic to humans. The National Toxicology Program's ("NTP's") Sixth Annual Report on Carcinogens, 1991, lists crystalline silica (respirable) as a substance which may reasonably be anticipated to be a carcinogen. In humans, a number of studies have found an association between lung cancer and exposure to dust containing respirable crystalline silica. In many of these studies, though not all, lung cancer risks were elevated and could not be explained by confounding factors such as cigarette smoking or arsenic or radon inhalation. While the IARC working group concluded there was sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite, it noted that carcinogenicity in humans was not detected in all circumstances studied. **NOTE:** The State of California requires the following statement: "Airborne particles of respirable size of crystalline silica are known to the State of California to cause cancer."

INGESTION: Nausea may result from accidental ingestion. May cause cancer.

EYE: Inflammation of eye tissue may occur from overexposure.

SKIN CONTACT/ABSORPTION: Inflammation from contact with open cuts may occur.

SIGNS AND SYMPTOMS ASSOCIATED WITH EXPOSURE OVER THE TLV:

Short Term: Shortness of breath, coughing associated with inhalation of dust. Long Term: May cause silicosis, a chronic disease of the lungs marked by acute fibrosis; may cause cancer.

EMERGENCY/FIRST AID PROCEDURES:

INHALATION: Move to fresh air; consult physician and /or obtain competent medical assistance as necessary.

INGESTION: Consult physician and/or obtain competent medical assistance.

EYE CONTACT: Flush with water; consult physician and/or obtain competent medical assistance as necessary.

REACTIVITY DATA

Stability: Stable

Incompatibility: None

Hazardous Polymerization: Will not occur.

SPILL OR LEAK PROCEDURES

If uncontaminated, recover and reuse. If contaminated, collect in suitable containers for disposal. Use appropriate method to avoid creating dust. Avoid breathing dust. Wear a NIOSH/MSHA/OSHA approved respirator.

CONDITIONS FOR SAFE USE

VENTILATION: Local exhaust required for dust removal. Refer to OSHA 1910.24, ASTM, and/or ANSI Standards. Do not exceed OSHA PEL or ACGIH TLV.

RESPIRATORY PROTECTION: Use NIOSH/MSHA/OSHA approved respirator if dust is present.

EYE PROTECTION: Optional, but recommended. NIOSH recommends against wearing contact lenses when working with crystalline silica.

PROTECTIVE GLOVES: Optional, but recommended.

SPECIAL PRECAUTIONS

1. Do not breathe dust.
2. Avoid creating dust in closed areas.
3. Use adequate ventilation as recommended by NIOSH/MSHA/OSHA for crystalline silica.

OTHER RELATED INFORMATION

NPCA / CPMA HMIS Ratings: Health (2) Flammability (0) Reactivity (0) Personal Protection (E)

Government regulations require that personnel working with crystalline silica receive appropriate training in safe work habits, respiratory protection and health risks.

The information and data contained herein are believed to be accurate, but the manufacturer makes no warranty with respect thereto and disclaims responsibility for reliance thereon.

Chem Clay Corporation makes no warranties, express or implied, concerning this product. No warranty for fitness of any particular purpose is made and we assume no responsibility whatever for any use of this product. The product should be used by properly trained personnel and in compliance with applicable health and safety laws and regulations.