



# MATERIAL SAFETY DATA SHEET

PRODUCT: Powder  
REVISION NUMBER: 1

REVISION DATE: 03/11/2005  
Date Printed: 03/11/2005

## 1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: Ferro Corporation  
251 West Wylie Avenue  
P.O. Box 519  
Washington, PA 15301  
Prod Info 724-223-5900  
CHEMTREC 800-424-9300

Use the CHEMTREC telephone number only in the event of chemical emergencies.

PREPARED BY: G. Myers  
PRODUCT CODE: J88749600  
PRODUCT TRADE NAME: 270 496 INTENSIVE RED  
CAS NO: Mixture  
CHEMICAL FAMILY: Pigment and Silica Mixture  
PRODUCT TYPE: Clayware Stains

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product does not have exposure limit values. Exposure limit values for some of the components are listed below as a guideline for safe use of this product.

### HAZARDOUS COMPONENTS

INGREDIENTS/CAS #	OSHA PEL:	ACGIH TLV:
Crystalline Silica 14808-60-7	TWA (Total Dust): 30 mg/m <sup>3</sup> / (%Quartz + 2) TWA (Resp. Frt): 250 mppcf / (%Quartz + 5) STEL (Resp. Frt.): 10 mg/m <sup>3</sup> / (%Quartz + 2)	TWA: Respirable Fraction: 0.05 mg/m <sup>3</sup>
Cadmium Compound NONE	TWA as Cd 0.005 mg/m <sup>3</sup>	TWA as Cd 0.01 mg/m <sup>3</sup> Respirable Fraction 0.002 mg/m <sup>3</sup>
Selenium Compound NONE	TWA as Se: 0.2 mg/m <sup>3</sup>	TWA as Se: 0.2 mg/m <sup>3</sup>

## 3. HAZARDS IDENTIFICATION

**PRINCIPLE ROUTES OF EXPOSURE:** Inhalation, ingestion and dermal.

**The key immediate hazards are:**

Skin, eye, and respiratory irritant

**Effects from Acute Exposure:**

**EYE CONTACT :** Causes eye irritation.

**PRODUCT TRADE NAME: 270 496 INTENSIVE RED**

- SKIN CONTACT:** Causes skin irritation.
- INHALATION:** Causes lung irritation.
- INGESTION:** May be harmful if swallowed.

**AGGRAVATED MEDICAL CONDITIONS:**

Respiratory conditions.

Populations at increased risk to cadmium include individuals with kidney disease, genetic differences in induction of metallothionein and dietary deficiencies in metal ions and/or protein.

**Effects from Chronic Exposure:**

**CARCINOGENIC INGREDIENTS:**

This product contains greater than 0.1% crystalline silica. The International Agency for Research on Cancer (IARC) has determined that "there is sufficient evidence for the carcinogenicity of crystalline silica to experimental animals and limited evidence of carcinogenicity in humans. "The National Toxicology Program (NTP) Sixth Annual Report confirms this determination. It has listed crystalline silica as a substance reasonably anticipated to be a carcinogen.

Cadmium & cadmium compounds: "The evidence for the carcinogenicity of NTP (1983): Cadmium and certain cadmium compounds in experimental animals is sufficient; the evidence of carcinogenicity in humans is limited." (IARC) "cadmium chloride, oxide, sulfate, and sulfide are carcinogenic in rats, causing local sarcomas after subcutaneous injection. Cadmium powder and cadmium sulfide produce local sarcomas in rats following intramuscular administration..."(IARC).

**OVEREXPOSURE EFFECTS:**

**CONTAINS CRYSTALLINE SILICA:**

Crystalline silica can cause silicosis, a lung disease characterized by coughing, wheezing, impaired lung function and increased sputum production. This damage can be progressive and may cause death. May cause cancer following repeated and prolonged inhalation of the fine dust. Smoking aggravates these effects. Skin and eye contact may cause irritation due to mechanical abrasion.

**CONTAINS CADMIUM COMPOUNDS:**

Overexposure to cadmium by inhalation can result in a metallic taste in the mouth, headache, shortness of breath, chest-pain, weakness, leg pains and fluid in the lungs. These signs and symptoms may be delayed, sometimes occurring four to eight hours following exposure. Kidney and liver damage may also occur. Swallowing can result in severe nausea, vomiting, diarrhea, stomach cramps, salivation, headache, muscle cramps, and dizziness.

Long term overexposure to the fumes and dust of cadmium have been associated with emphysema, bronchitis and kidney damage. Chronic overexposure to the metal and cadmium compounds, such as cadmium oxide, cadmium sulfide, cadmium sulfate and cadmium chloride, may result in lung cancer, although a definite cause-effect relationship has not been fully established.

## 4. FIRST AID MEASURES

**INGESTION:** If swallowed, give at least 3-4 glasses of water, but do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

**SKIN:** For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

**INHALATION:** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

**EYES:** For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention if irritation develops.

**NOTES TO PHYSICIAN:** Use of this product is regulated by the OSHA Cadmium Standard (29 CFR 1910.1027). The extensive medical surveillance and worker removal provisions of this standard should be consulted. Cadmium and its inorganic compounds are harmful to the kidneys and lungs.

## 5. FIRE FIGHTING MEASURES

**FLASH POINT (°F):** Not Applicable

**Lower Explosive Limit:** Not Available

**Upper Explosive Limit:** Not Available

**EXTINGUISHING MEDIA:** Water

**FIRE FIGHTING PROCEDURES:** Fire-Fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.

Use water spray to cool nearby containers and structures exposed to fire.

**UNUSUAL HAZARDS:** This product will not burn. Use appropriate techniques for fighting surrounding fire.

## 6. ACCIDENTAL RELEASE MEASURES

**SPILL PROCEDURES:** Wear appropriate protective equipment. Avoid the generation of dust. Vacuum or shovel material and place in closable container(s) for disposal.

Dry sweeping of cadmium containing dust is a violation of the OSHA Cadmium Standard (29 CFR 1910.1027).

For clean up of cadmium containing products, HEPA (high efficiency particulate air purifying) filtered vacuuming equipment or equally effective filtration methods shall be used and emptied in a manner that minimizes the re-entry of cadmium into the workplace.

## 7. HANDLING AND STORAGE

**PRODUCT TRADE NAME: 270 496 INTENSIVE RED**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Avoid contact with eyes, skin and clothing.

**NOTES ON HANDLING INFORMATION:** Minimize dust generation during handling. Use adequate ventilation.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**VENTILATION:** Adequate ventilation should be provided to keep concentrations below acceptable Exposure Limits. Discharge from the ventilation system should comply with the applicable air pollution control regulations.

If air from exhaust ventilation is recirculated into the workplace, the system shall have a high efficiency filter and be monitored to assure effectiveness in accordance with the OSHA Cadmium Standards (29 CFR 1910.1027).

**EYE PROTECTION:** Wear safety glasses or goggles to protect against exposure.

**PROTECTIVE GLOVES:** Use gloves as a standard industrial handling procedure.

**RESPIRATORY PROTECTION:** Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

**OTHER PERSONAL PROTECTIVE EQUIPMENT:** None specified.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Red Powder

**BOILING POINT:** Not Applicable

**VAPOR DENSITY (AIR=1):** Non-Volatile

**EVAP. RATE(BUTYL ACETATE=1):** Non-Volatile

**VOC, Wt.% (EPA METH.24):** 0

**BULK DENSITY:** Not Available

**SOLUBILITY (in water):** Insoluble

## 10. STABILITY AND REACTIVITY

**STABILITY DATA:** STABLE

**POLYMERIZATION:** WILL NOT OCCUR

**HAZARDOUS DECOMPOSITION PRODUCTS:** Contains cadmium sulfide and/or cadmium sulfoselenide pigments, depending upon conditions; oxides of sulfur, cadmium and/or selenium may form.

**PRODUCT TRADE NAME: 270 496 INTENSIVE RED**

**INCOMPATIBILITY**

(MATERIALS TO AVOID): None known.

CONDITIONS/HAZARDS TO AVOID: None known.

**11. TOXICOLOGICAL INFORMATION**

No Toxicological data known.

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** No data at this time

**CHEMICAL FATE INFORMATION:** No data at this time.

**PERSISTENCE/DEGRADABILITY:** No data at this time.

**APPRAISAL:** No data at this time.

**MOBILITY:** No data at this time.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL OF WASTE METHOD:** Dispose in accordance with Federal, State and Local regulations.

**14. TRANSPORT INFORMATION**

**DOT Shipping Name:** DOT data is available upon request. Contact the Environmental, Health, & Safety Department at (724) 223-5900.

**15. REGULATORY INFORMATION**

**SARA SECTION 302:** None Found

**SARA (311, 312) HAZARD CLASS:** ACUTE HEALTH HAZARD

CHRONIC HEALTH HAZARD

**SARA 313 Title III Toxic Chemical List:**

The following chemicals are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

85	%	Cadmium compounds, n.o.s.	< 1	%	Metal as Cd
85	%	Selenium compounds	< 1	%	Metal as Se

**TSCA Inventory Status:** This product (and/or all of its components) is in compliance with the U.S. EPA Toxic Substance Control Act, TSCA, (15 U.S.C. 2604).

This product and all of its components is listed on the DSL inventory.

**16. OTHER INFORMATION**

**Revisions:** The Format has been changed to meet the requirements of the new ANSI Standard Z400.1.

**PRODUCT TRADE NAME: 270 496 INTENSIVE RED**

**LABEL INFORMATION:**

**DANGER!**

Contains cadmium which is a cancer hazard. Cadmium can cause lung and kidney disease.

Skin, eye, and respiratory irritant.

Contains crystalline silica which can cause lung damage, including cancer.

Avoid contact with eyes, skin and clothing.

Do not breathe dust.

Keep away from food products.

Wash thoroughly after handling and before eating, drinking or using cosmetic or tobacco products or toilet facilities.

Handle in accordance with the OSHA Cadmium Standard.

Use with adequate ventilation.

Keep container closed when not in use.

**FIRST AID:** If inhaled, remove to fresh air. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water. Remove contaminated clothing. Get medical attention.

**IN CASE OF FIRE:** Use water, dry chemical or carbon dioxide.

**IN CASE OF SPILL:** Collect and dispose in accordance with federal, state and local regulations.

**FOR INDUSTRIAL USE ONLY.**

**DEFINITIONS AND ABBREVIATIONS :**

ACGIH = American Conference of Governmental Industrial Hygienists

C (CEIL) = The concentration that shall not be exceeded during any part of the working exposure.

CAS # = Chemical Abstracts Service Registry Number

EPA = Environmental Protection Agency

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

SARA = Superfund Amendments and Reauthorization Act

STEL = Short Term Exposure Limit. Usually a 15 minute time weighted average exposure.

TLV = Threshold Limit Values

TSCA = Toxic Substance Control Act

TWA = Time Weighted Average. Exposure concentration for a normal 8 hour day or 40 hour week.

VOC = Volatile Organic Content

**DISCLAIMER:** The information contained in this Material Safety Data Sheet (MSDS) has been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No guarantee is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine the regulatory compliance obligations under any applicable federal or state laws.

**\*\*\* END OF MSDS \*\*\***